



ATLAS METAL

1135 N.W. 159th DRIVE, MIAMI, FLORIDA 33169

TEL 305.625.2451

TOLL FREE 800.762.7565

FAX 305.623.0475

WWW.ATLASFOODSERV.COM

SALES@ATLASFOODSERV.COM

Project: _____

Item No.: _____

Quantity: _____

SELF LEVELING DISPENSERS



MOPD2-6-1/2

PLATE DISPENSER

Mobile Open Plate Dispenser

- MOPD2
- MOPD2H
- MOPD3
- MOPD3H
- MOPD4
- MOPD4H

SPECIFICATIONS

The MOPD series frame shall be constructed of 1" stainless steel tubing, welded to a 16 gauge stainless steel upper and lower deck, with heavy duty reinforcements to support the weight of the dish tubes. The heated MOPD frame shall have in addition a receptacle attached to the underside of the upper deck with a six foot cordset.

DISPENSING TUBE UNHEATED: The basic unit shall be constructed of 300 series stainless steel, the counter top flange has three high impact plastic guide posts to align plates, the unit is self supporting using a formed stainless steel flange welded to vertical channels and a bottom disc, stainless steel platform will be suspended with extension springs to support the stack of plates to be dispensed. With an additional stainless steel jacket to cover spring mechanism and channel guides.

DISPENSING TUBE HEATED: Same construction with the addition of a base mounted heating element, a side mounted thermostat, pilot light and on-off switch located in the top flange, a 6' 120V NEMA 5-15P cord set.

SELF LEVELING: The spring mechanism is easy to adjust. A combination of extension springs will be provided for field adjustment to the required dispensing height.

CASTERS: Shall be 4" swivel heavy duty with optional brake.

Specifications subject to change without notice.

STANDARD FEATURES

- Field Adjustable for different weights
- All stainless steel construction
- High impact plastic guide posts to align plates
- Capacity up to (72) plates or (36) bowls*
- UL Listed & NSF Approved

ACCESSORIES

- Modify tube depth
- 220/240 volt operation (specify)
- Stainless steel trays to convert PD-12 to cup dispenser
- Stainless steel pre-heat tube covers
- LB - Locking brakes (set of 2)
- WB - Wrap around bumpers
- Corner bumpers, 3" dia. (set of 4)(non rotating)
- Rotary bumpers, 4" dia. (set of 4)



2-STACK MOBILE OPEN PLATE DISPENSER						
MAX. DISH DIA.	2-STACK UNDEHEATED	L X W	SHIP WT. (lbs.)	2-STACK HEATED	120V/ELEC WATTS/AMPS	SHIP WT. (lbs.)
5"	MOPD2-5	24-5/8" X 15-1/8" (62.5 X 38.4cm)	80 (36.2kg)	MOPD2H-5	420 3.5	90 (40.8kg)
5-3/4"	MOPD2-5-3/4	24-5/8" X 15-1/8" (62.5 X 38.4cm)	86 (39kg)	MOPD2H-5-3/4	480 4.0	99 (44.9kg)
6-1/2"	MOPD2-6-1/2	24-5/8" X 15-1/8" (62.5 X 38.4cm)	88 (39.9kg)	MOPD2H-6-1/2	540 4.5	100 (45.3kg)
7-1/4"	MOPD2-7-1/4	24-5/8" X 15-1/8" (62.5 X 38.4cm)	91 (41.2kg)	MOPD2H-7-1/4	600 5.0	106 (48kg)
8-1/8"	MOPD2-8-1/8	30-3/8" X 16-1/8" (77.1 X 40.9cm)	105 (47.6kg)	MOPD2H-8-1/8	660 5.5	110 (49.8kg)
9-1/8"	MOPD2-9-1/8	30-3/8" X 16-1/8" (77.1 X 40.9cm)	108 (48.9kg)	MOPD2H-9-1/8	760 6.3	113 (51.2kg)
10-1/8"	MOPD2-10-1/8	30-3/8" X 16-1/8" (77.1 X 40.9cm)	112 (50.8kg)	MOPD2H-10-1/8	840 7.0	117 (53kg)
12"	MOPD2-12	34-1/8" X 18" (86.6 X 45.7cm)	120 (54.4kg)	MOPD2H-12	1000 8.3	125 (56.6kg)
14-1/2"	MOPD2-14-1/2	38-5/8" X 20" (98 X 50.8cm)	159 (72.1kg)	MOPD2H-14-1/2	1100 9.0	158 (71.6kg)



3-STACK MOBILE OPEN PLATE DISPENSER						
MAX. DISH DIA.	3-STACK UNDEHEATED	L X W	SHIP WT. (lbs.)	3-STACK HEATED	120V/ELEC WATTS/AMPS	SHIP WT. (lbs.)
5"	MOPD3-5	36" X 15-1/8" (91.4 X 38.4cm)	105 (47.6kg)	MOPD3H-5	630 5.3	115 (52.1kg)
5-3/4"	MOPD3-5-3/4	36" X 15-1/8" (91.4 X 38.4cm)	111 (50.3kg)	MOPD3H-5-3/4	720 6.0	124 (56.2kg)
6-1/2"	MOPD3-6-1/2	36" X 15-1/8" (91.4 X 38.4cm)	114 (51.7kg)	MOPD3H-6-1/2	810 6.8	126 (57.1kg)
7-1/4"	MOPD3-7-1/4	36" X 15-1/8" (91.4 X 38.4cm)	116 (52.6kg)	MOPD3H-7-1/4	900 7.5	140 (63.5kg)
8-1/8"	MOPD3-8-1/8	44-5/8" X 16-1/8" (115.8 X 40.9cm)	138 (62.5kg)	MOPD3H-8-1/8	990 8.3	150 (68kg)
9-1/8"	MOPD3-9-1/8	44-5/8" X 16-1/8" (115.8 X 40.9cm)	142 (64.4kg)	MOPD3H-9-1/8	1140 9.5	158 (71.6kg)
10-1/8"	MOPD3-10-1/8	44-5/8" X 16-1/8" (115.8 X 40.9cm)	146 (66.2kg)	MOPD3H-10-1/8	1260 10.5	160 (72.5kg)
12"	MOPD3-12	50-1/4" X 18" (127.6 X 45.7cm)	170 (77.1kg)	MOPD3H-12	1500 12.5	185 (83.9kg)
14-1/2"	MOPD3-14-1/2	57-1/4" X 20" (145.4 X 50.8cm)	226 (102.5kg)	MOPD3H-14-1/2	1650 13.5	232 (105.2kg)



4-STACK MOBILE OPEN PLATE DISPENSER						
MAX. DISH DIA.	4-STACK UNDEHEATED	L X W	SHIP WT. (lbs.)	4-STACK HEATED	120V/ELEC WATTS/AMPS	SHIP WT. (lbs.)
5"	MOPD4-5	24-5/8" X 24-5/8" (62.5 X 62.5cm)	125 (56.6kg)	MOPD4H-5	840 7.0	151 (68.4kg)
5-3/4"	MOPD4-5-3/4	24-5/8" X 24-5/8" (62.5 X 62.5cm)	134 (60.7kg)	MOPD4H-5-3/4	960 8.0	163 (73.9kg)
6-1/2"	MOPD4-6-1/2	24-5/8" X 24-5/8" (62.5 X 62.5cm)	143 (64.8kg)	MOPD4H-6-1/2	1080 9.0	165 (74.8kg)
7-1/4"	MOPD4-7-1/4	24-5/8" X 24-5/8" (62.5 X 62.5cm)	145 (65.7kg)	MOPD4H-7-1/4	1200 10.0	167 (75.7kg)
8-1/8"	MOPD4-8-1/8	30-3/8" X 30-3/8" (77.1 X 77.1cm)	175 (79.3kg)	MOPD4H-8-1/8	1320 11.0	184 (83.4kg)
9-1/8"	MOPD4-9-1/8	30-3/8" X 30-3/8" (77.1 X 77.1cm)	180 (81.6kg)	MOPD4H-9-1/8	1520 12.7	188 (85.2kg)
10-1/8"	MOPD4-10-1/8	30-3/8" X 30-3/8" (77.1 X 77.1cm)	188 (85.2kg)	MOPD4H-10-1/8	1680 14.0	194 (87.9kg)
12"	MOPD4-12	34-1/8" X 34-1/8" (86.6 X 86.6cm)	218 (98.8kg)	MOPD4H-12	2000 16.7	226 (102.5kg)
14-1/2"	MOPD4-14-1/2	38-5/8" X 38-5/8" (98 X 98cm)	291 (131.9kg)	MOPD4H-14-1/2	2200 18.0	287 (130.1kg)